(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



I 1800 THUSIDI IL EISHID HAN OSIN OSINI ONI I II NI BARDI ISHO NOSI SHIKO NIDELTIK KILISO KAN HAN

(43) International Publication Date 9 September 2005 (09.09.2005)

PCT

(10) International Publication Number WO 2005/082538 A1

(51) International Patent Classification7:

B02C 2/04

(21) International Application Number:

PCT/GB2005/000684

(22) International Filing Date: 24 February 2005 (24.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0404263.6 0404879.9 26 February 2004 (26.02.2004) GB 4 March 2004 (04.03.2004) GB

(71) Applicant (for all designated States except US): EXTEC SCREENS & CRUSHERS LIMITED [GB/GB]; Hearth-

(72) Inventor; and

(75) Inventor/Applicant (for US only): WAGSTAFFE,


cote Road, Swadlincote, Derbyshire DE11 9DU (GB).

Christopher, William [GB/GB]; Hearthcote Road, Swadlincote, Derbyshire DE11 9DU (GB).

- (74) Agent: ORR, William, McLean; Urquhart-Dykes & Lord LLP, Tower North Central, Merrion Way, Leeds LS2 8PA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: CONE CRUSHER



(57) Abstract: A cone crusher (20) which comprises: a bowl (4) having a concave liner (3); a head (2) having a mantle (1) and which is capable of carrying out gyratory movement within the bowl (4) so that the concave liner (3) and the mantle (1) define a generally annular crushing space and cooperate to exert a crushing action on crushable material in such space; and a drive train coupled with the head (2) and operative to apply gyratory movement thereto; in which the drive train comprises: an upright drive shaft (15); an eccentric (9) mounted on, and arranged to be driven by the drive shaft (15), said head 82) being mounted on the eccentric (9) in such a way that the head is driven to carry out gyratory movement within the bowl (4); and a drive motor (14) coupled with a lower end of the drive shaft (15), said motor having a small lateral extent, measured radially outwardly of the axis of the drive shaft (15), so as to present minimum obstacle to direct downward gravity discharge of crushed material from the crushing space defined between the concave liner (3) and the mantle (1).